



Technical drawing of a hexagonal plate with a central circular hole and six smaller holes at the vertices. The drawing includes the following dimensions and features:

- Outer diameter: $\varnothing 102$
- Inner diameter: $\varnothing 90$
- Corner radius: $R5$
- Hole diameter: $\varnothing 7$
- Overall width: 106



| | | | | | | | | | | | | | | | | | | |
|--|------------------|---------------|----------------|------------------|-------------------|--------------------|---------------------|---------------------|-----------------------|---------------|----------------|------------------|-------------------|----------------------------|-----------------|------------------|-------------------|--------------|
| Corresponding symbols | | | | | | | | | | ▽ | ▼ | ▽▽ | ▼▼ | ▽▽▽ | ▼▼▼ | | | |
| Roughness Classes (NBN 88-02) (ISO 1302) | | | | | | | | | N11 | N10 | N9 | N8 | N7 | N6 | N5 | N4 | | |
| Roughness Value "Ra" in µm (NBN 88-02) (ISO 1302) | | | | | | | | | 25 | 12,5 | 6,3 | 3,2 | 1,6 | 0,8 | 0,4 | 0,2 | | |
| Allowable deviations for dimensions without tolerance indication (machined surfaces) | | | | | | | | | | | | | | | | | | |
| For measurements (deviations in mm) | | | | | | | | | Filletts and chamfers | | | | | Angles (in ° and ') | | | | |
| Accuracyclass (ISO 2768.1) | Dimensions in mm | | | | | | | | Dimensions in mm | | | | | Length of the shortest leg | | | | |
| | 0,5 to 3 | >3 to 6 | >6 to 30 | >30 to 120 | >120 to 400 | >400 to 1000 | >1000 to 2000 | >2000 to 4000 | 0,5 to 3 | >3 to 6 | >6 to 30 | >30 to 120 | >120 to 400 | to 10 | >10 to 50 | >50 to 120 | >120 to 400 | above 400 |
| f Fine | ±0,05 | ±0,05 | ±0,1 | ±0,15 | ±0,2 | ±0,3 | ±0,5 | ±0,8 | ±0,2 | ±0,5 | ±1 | ±2 | ±4 | ±1° | ±30' | ±20' | ±10' | ±5' |
| m Medium | ±0,1 | ±0,1 | ±0,2 | ±0,3 | ±0,5 | ±0,8 | ±1,2 | ±2 | | | | | | | | | | |
| c Rough | ±0,2 | ±0,3 | ±0,5 | ±0,8 | ±1,2 | ±2 | ±3 | ±4 | ±0,4 | ±1 | ±2 | ±4 | ±8 | ±1°30' | ±1° | ±30' | ±15' | ±10' |
| v Very Rough | - | ±0,5 | ±1 | ±1,5 | ±2,5 | ±4 | ±6 | ±8 | | | | | | ±3° | ±2° | ±1° | ±30' | ±20' |

| | | | | | |
|---|------|---------------------------|-----------|------------|--|
| | | | | | |
| | | | | | |
| Revision | Date | Description | | | |
| Engineered by: Galba, J. | | | Name: | Date: | Scale: 1:1 |
| | | Designer: | Galba, J. | 26/03/2011 | SheetSize: A3 |
| | | Approved: | Galba, J. | 26/03/2011 | |
| Project: Miniature Model Engine | | | | | Material: Rubber |
| | | | | | Total Mass: 0,003 kg |
| Title: 6 Cylinder - Radial Engine (Pneumatic) Crankcase Gasket | | | | | |
|  | | Drawingnumber: | | | Sheet: 0001 |
| | | Design State: Released | | | Drawing made with autodesk Inventor Revisions only permitted by CAD |

This document is for educational purposes only and property of Inventor Wizard. It shall not without our permission be altered, copied, used for manufacturing or communicated to any other person or company.