



Break Sharp Edges: 0,1 mm

Revision	Date	Description				
Engineered by: Galba, J.			Name:	Date:	Scale: 2:1	
		Designer:	Galba, J.	26/03/2011	SheetSize: A3	
		Approved:	Galba, J.	26/03/2011		
Project: Miniature Model Engine					Material:	Brass, Soft Yellow
					Total Mass: 0,075 kg	
Title: 6 Cylinder - Radial Engine (Pneumatic) Connecting Rod Hub						
 InventorWizard.be/.nl		Drawingnumber:				Sheet: 0001
		Design State:				Drawing made with autodesk Inventor Revisions only permitted by CAD
		Released				

Corresponding symbols								
Roughness Classes ( NBN 88-02 ) ( ISO 1302 )								
Roughness Value "Ra" in µm ( NBN 88-02 ) ( ISO 1302 )								
	N11	N10	N9	N8	N7	N6	N5	N4
	25	12,5	6,3	3,2	1,6	0,8	0,4	0,2
Allowable deviations for dimensions without tolerance indication (machined surfaces)								
For measurements ( deviations in mm )								
Accuracyclass (ISO 2768.1)	Dimensions in mm							
	0,5 to 3	>3 to 6	>6 to 30	>30 to 120	>120 to 400	>400 to 1000	>1000 to 2000	>2000 to 4000
f Fine	±0,05	±0,05	±0,1	±0,15	±0,2	±0,3	±0,5	±0,8
m Medium	±0,1	±0,1	±0,2	±0,3	±0,5	±0,8	±1,2	±2
c Rough	±0,2	±0,3	±0,5	±0,8	±1,2	±2	±3	±4
v Very Rough	-	±0,5	±1	±1,5	±2,5	±4	±6	±8
Fillet and chamfers								
Dimensions in mm								
	0,5 to 3	>3 to 6	>6 to 30	>30 to 120	>120 to 400			
	±0,2	±0,5	±1	±2	±4			
Angles ( in ° and ' )								
Length of the shortest leg								
	to 10	>10 to 50	>50 to 120	>120 to 400	above 400			
	±1°	±30'	±20'	±10'	±5'			
	±1°30'	±1°	±30'	±15'	±10'			
	±3°	±2°	±1°	±30'	±20'			

This document is for educational purposes only and property of Inventor Wizard.  
It shall not without our permission be altered, copied, used for manufacturing or  
communicated to any other person or company.